

Product Informations

Updated: 12/02/2022

HF adhesive label, white paper version, size mm.40x20, standard adhesive, OFF metal use.

Services available for custom printing and coding

Option: Black or CMYK colors printing, barcode / QR / Logos - User memory encoding - Special packaging - Custom label dimensions

Variants: Versions on request: WET IN-LAY (Transparent PET) or White PET printable or with 3M special ADHESIVES

Electrical Tag features:	Frequency	Reading distance	Chip Type	EPC-UID	User Memory
HF	13,56 MHz	Up to 1-8 Cm.	ICODE SLIX	7 Byte	896 bits-112 Byte
	ISO standard 15693 /18000-3M1 (NFC T5T)	Operating temp.C° -40/+85 °C	Storage temp.C° -50/+125 °C	EPC Access-pass ND	Data Retent. 50 years

Optional Chip: ICode SLIX, Icode SLIX_2

Label Physical features

Antenna of Tag

Size Label mm

40x20

Surface Material

White paper

Adhesive

Standard Adhesive

Mounting

OFF Metal

Size Antenna mm.

26X12




Standard Packaging

"L" Width
40 mm.

"A" Height
20 mm.

"Step"
mm.

Liner
mm.




single-row roll

Pcs
Roll:
Outer
Diam. mm
Internal
Diam. mm

76

Cross-Section Label



Packaging Notes: