

Product Informations

Updated: 12/02/2022

HF adhesive label, white PET version, size mm.40x20, standard adhesive, OFF metal use.

Services available for custom printing and coding

Option: Black or CMYK colors printing, barcode / QR / Logos - User memory encoding - Special packaging - Custom label dimensions

Variants: Versions on request: WET IN-LAY (Transparent PET) or printable White PAPER or with special 3M ADHESIVES

Electrical Tag features:	Frequency	Reading distance	Chip Type	EPC-UID	User Memory
<b>HF</b>	<b>13,56 MHz</b>	Up to <b>1-8</b> Cm.	<b>ICODE SLIX</b>	<b>7 Byte</b>	<b>896 bits-112 Byte</b>
	ISO standard <b>15693 /18000-3M1 (NFC T5T)</b>	Operating temp.C° <b>-40/+85 °C</b>	Storage temp.C° <b>-50/+125 °C</b>	EPC Access-pass <b>ND</b>	Data Retent. <b>50 years</b>

Optional Chip: ICode SLIX, Icode SLIX\_2

Label Physical features

Antenna of Tag

Size Label mm

**40x20**

Surface Material

**White PET**

Adhesive

**Standard Adhesive**

Mounting

**OFF Metal**

Size Antenna mm.

**26X12**




Standard Packaging

"L" Width  
**40** mm.

"A" Height  
**20** mm.

"Step"  
mm.

Liner  
mm.




single-row roll

Pcs  
Roll:  
Outer  
Diam. mm  
Internal  
Diam. mm

**76**

Cross-Section Label



Packaging Notes: