

Product Informations

Updated: 12/02/2022

HF adhesive label, ANTIMETAL white PET + Clear RESIN, size mm.Diam.25, with 3M 467-MP adhesive, ON/OFF metal use.

RESINED "ON / OFF Metal" NFC/HF tag, covered with transparent resin. Services available for custom printing and coding

Option: Black or CMYK colors printing, barcode / QR / Logos - User memory encoding - Special packaging - Custom label dimensions

Variants: Versions on request with special 3M ADHESIVES

Electrical Tag features:	Frequency 13,56 MHz	Reading distance Up to 1-5 Cm.	Chip Type ICode SLIX	EPC-UID 7 Byte	User Memory 896 bits-112 Byte
HF	ISO standard 15693 /18000-3M1 (NFC T5T)	Operating temp.C° -40/+85 °C	Storage temp.C° -50/+125 °C	EPC Access-pass ND	Data Retent. 50 years

Optional Chip: ICode SLIX, Icode SLIX_2

Label Physical features

Antenna of Tag

Size Label mm

Diam.25

Surface Material

PET+PU RESIN

Adhesive

**3M 467-MP (80
microns)**

Mounting

ON/OFF Metal

Size Antenna mm.

Diam. 22



Standard Packaging

Cross-Section Label

Front tag
Clear Resin
Custom printing
White PET/PP
Inlay Antenna + Chip (Clear PET)
0,2 mm antimetal material
3M 467-MP Adhesive (80 microns)
Release Liner
Back tag

Packaging Notes:

Single product in bags