


Features of standard products								
	A1-H Series	A2-H Series	A3-H Series	A4-H Series	S1-H Series	S2-H Series	S3-H Series	S4-H Series
Size MM.	33x27x6	32x17x3,5	36x16x5,5	Diam.20x6	60x25x6	65x25x6	48x25x6	75x25x6
Mounting	Screw or rivets	adhesive	Plastic Ties, screws	adhesive	Pendant	Screw or rivets	Adhesive	Plastic/metal Ties
Compatible materials	All materials + Metals	All materials + Metals	All materials + Metals	All materials + Metals	All materials + Metals	All materials + Metals	All materials + Metals	All materials + Metals
Reading distance	1-20cm	1-20cm	1-20cm	1-20cm	1-20cm	1-20cm	1-20cm	1-20cm
Frequency of Tag	13,56 MHz	13,56 MHz	13,56 MHz	13,56 MHz	13,56 MHz	13,56 MHz	13,56 MHz	13,56 MHz
ISO Protocol	15693	15693	15693	15693	15693	15693	15693	15693
STD Chip	SLIX	SLIX	SLIX	SLIX	SLIX	SLIX	SLIX	SLIX
UID	7 Byte	7 Byte	7 Byte	7 Byte	7 Byte	7 Byte	7 Byte	7 Byte
User Memory	1024 bits	1024 bits	1024 bits	1024 bits	1024 bits	1024 bits	1024 bits	1024 bits
IP Protection	IP65	IP65	IP65	IP65	IP68	IP68	IP68	IP68
Optional Chips	Different chips for MOQ: SLIX2	Different chips for MOQ: SLIX2	Different chips for MOQ: SLIX2	Different chips for MOQ: SLIX2	Different chips for MOQ: SLIX2	Different chips for MOQ: SLIX2	Different chips for MOQ: SLIX2	Different chips for MOQ: SLIX2
Wintag Order Code:	Available Variants A1-HB	Available Variants A2-HB	Available Variants A3-HB	Available Variants A4-HB	Available Variants S1-H1	Available Variants S2-H1	Available Variants S3-H1	Available Variants S4-H1
Description	A1-HB HF made in Nylon GF Basic IP65, usable -40°/+120°	A2-HB HF made in ABS basic, usable -40°/+80°	A3-HB HF made in Nylon FV basic, usable -40°/+80°	A4-HB HF made in Nylon FV basic, usable -40°/+80°	S1-H1 HF made in ABS Resined IP68, usable -40°/+80°	S2-H1 HF made in ABS Resined IP68, usable -40°/+80°	S3-H1 HF made in ABS Resined IP68, usable -40°/+80°	S4-H1 HF made in ABS Resined IP68, usable -40°/+80°
Materiale housing:	Nylon GF+PU resin	ABS	Nylon GF	Nylon GF	ABS+PU resin	ABS+PU resin	ABS+PU resin	ABS+PU resin
Wintag Order Code:	A1-H3		A3-H2	A4-H3	S1-H2	S2-H2	S3-H2	S4-H2
Description	A1-H3 HF made in Nylon GF Resined IP68, usable -40°/+120°	#N/D	A3-H2 HF made in ASA Resined IP68, UV long time resistant, usable -40°/+80°	A4-H3 HF made in Nylon GF Resined IP68, usable -40°/+120°	S1-H2 HF made in ASA Resined IP68, UV resistant long time, usable -40°/+80°	S2-H2 HF made in ASA Resined IP68, UV resistant long time, usable -40°/+80°	S3-H2 HF made in ASA Resined IP68, UV resistant long time, usable -40°/+80°	S4-H2 HF made in ASA Resined IP68, UV resistant long time, usable -40°/+80°
Materiale housing:	Nylon GF+PU resin	#N/D	ASA+PU resin	Nylon GF+PU resin	ASA+PU resin	ASA+PU resin	ASA+PU resin	ASA+PU resin
Wintag Order Code:			A3-H3	A4-H5	S1-H3	S2-H3	S3-H3	S4-H3
Description	#N/D	#N/D	A3-H3 HF made in Nylon GF Resined IP68, usable -40°/+120°	A4-H5 HF made in Nylon FDA food-compliant, Resined IP68, usable -40°/+120°	S1-H3 HF made in Nylon GF Resined IP68, usable -40°/+120°	S2-H3 HF made in Nylon GF Resined IP68, usable -40°/+120°	S3-H3 HF made in Nylon GF Resined IP68, usable -40°/+120°	S4-H3 HF made in Nylon GF Resined IP68, usable -40°/+120°
Materiale housing:	#N/D	#N/D	Nylon GF+PU resin	Nylon GF+PU resin FDA	Nylon GF+PU resin	Nylon GF+PU resin	Nylon GF+PU resin	Nylon GF+PU resin
Wintag Order Code:			A3-H5		S1-H5	S2-H5	S3-H5	S4-H5
Description	#N/D	#N/D	A3-H5 HF made in Nylon FDA food-compliant, Resined IP68, usable -40°/+120°	#N/D	S1-H5 HF made in Nylon FDA food-compliant, Resined IP68, usable -40°/+120°	S2-H5 HF made in Nylon FDA food-compliant, Resined IP68, usable -40°/+120°	S3-H5 HF made in Nylon FDA food-compliant, Resined IP68, usable -40°/+120°	S4-H5 HF made in Nylon FDA food-compliant, Resined IP68, usable -40°/+120°
Materiale housing:	#N/D	#N/D	Nylon GF+PU resin FDA	#N/D	Nylon GF+PU resin FDA	Nylon GF+PU resin FDA	Nylon GF+PU resin FDA	Nylon GF+PU resin FDA

Features of standard products								
	F1-H Series	P2-H Series	P3-H Series	P3F-H Series	R1-H Series	M1-H Series	SL1-H Series	TT-H Series
Size MM.	68x45x10	75x26x3	95x36x4	95x36x4	Diam.30x20 F.10	83,5x36x18	38x25x11	varie/ various
Mounting	Plastic Ties, screws	Screw or rivets	Screw or rivets	Screw or rivets	Pressure	Magnetic	Metal cable	Cable tie
Compatible materials	All materials + Metals	All materials, NOT Metals	All materials, NOT Metals	All materials, NOT Metals	All materials + Metals	All materials + Metals	All materials + Metals	All materials, NOT Metals
Reading distance	1-20cm	1-20cm	1-20cm	1-20cm	1-20cm	1-20cm	1-20cm	1-20cm
Frequency of Tag	13,56 MHz	13,56 MHz	13,56 MHz	13,56 MHz	13,56 MHz	13,56 MHz	13,56 MHz	13,56 MHz
ISO Protocol	15693	15693	15693	15693	15693	15693	15693	14443A
STD Chip	SLIX	SLIX	SLIX	SLIX	SLIX	SLIX	SLIX	Ntag 213
UID	7 Byte	7 Byte	7 Byte	7 Byte	7 Byte	7 Byte	7 Byte	7 Byte
User Memory	1024 bits	1024 bits	1024 bits	1024 bits	1024 bits	1024 bits	1024 bits	144 Byte
IP Protection	IP68	IP68	IP68	IP68	IP68	IP68	IP65	IP65
Optional Chips	Different chips for MOQ: SLIX2	Different chips for MOQ: SLIX2	Different chips for MOQ: SLIX2	Different chips for MOQ: SLIX2	Different chips for MOQ: SLIX2	Different chips for MOQ: SLIX2	Different chips for MOQ: SLIX2	Different chips for MOQ: SLIX2
Wintag Order Code:	Available Variants F1-H1	Available Variants P2-H1	Available Variants P3-H1	Available Variants P3F-HM	Available Variants R1-H1	Available Variants M1-H1	Available Variants SL1-H1	Available Variants TT-H
Description	F1-H1 HF made in ABS Resined IP68, usable -40°/+80°	P2-H1 HF in ABS Resined IP68, utilizzo -40°/+80°	P3-H1 HF in ABS Resined IP68, utilizzo -40°/+80°	P3F-HM HF in gomma flessibile TPE molded IP68, molto resistente agenti chimici e UV, utilizzo -40°/+100°	Tag Bottone R1-H1 HF Diam. 30x20 mm. in Nylon IP68, resistente agenti chimici e UV, utilizzo -40°/+90°	Tag Magnetico M1-H1 HF IP68, ON/OFF metal, per superfici piane o tonde.	SL1-H1 Sigillo HF size mm.38x25x11 in ABS resistente con cavetto 280 mm	Disponibili in diverse misure, vedi datasheet
Materiale housing:	ABS+PU resin	ABS+PU resin	ABS+PU resin	TPE	Nylon	Nylon FV	ABS	Nylon
Wintag Order Code:	F1-H3	P2-H2	P3-H2					
Description	F1-H3 HF made in Nylon GF Resined IP68, usable -40°/+120°	P2-H2 HF made in ASA Resined IP68, UV long time resistant, usable -40°/+80°	P3-H2 HF made in ASA UV long time resistant, Resined IP68, usable -40°/+80°	#N/D	#N/D	#N/D	#N/D	#N/D
Materiale housing:	Nylon GF+PU resin	ASA+PU resin	ASA+PU resin	#N/D	#N/D	#N/D	#N/D	#N/D
Wintag Order Code:	F1-H5	P2-H3	P3-HM					
Description	F1-H5 HF made in Nylon FDA food-compliant, Resined IP68, usable -40°/+120°	P2-H3 HF made in Nylon GF Resined IP68, usable -40°/+120°	P3-HM HF made in PP+TPE molded IP68, chemical aggressive resistant, usable -40°/+110°	#N/D	#N/D	#N/D	#N/D	#N/D
Materiale housing:	Nylon GF+PU resin FDA	Nylon GF+PU resin	PP+TPE	#N/D	#N/D	#N/D	#N/D	#N/D
Wintag Order Code:		P2-H5						
Description	#N/D	P2-H5 HF made in Nylon FDA food-compliant, Resined IP68, usable -40°/+120°	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D
Materiale housing:	#N/D	Nylon GF+PU resin FDA	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D

Features of standard products		BR-H Series						
Size MM.	varie/ various	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D
Mounting	On Wrist	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D
Compatible materials	All materials, NOT Metals	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D
Reading distance	1-20cm	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D
Frequency of Tag	13,56 MHz	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D
ISO Protocoll	15693	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D
STD Chip	SLIX	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D
UID	7 Byte	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D
User Memory	1024 bits	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D
IP Protection	IP68	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D
Optional Chips	Different chips for MOQ: SLIX2	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D
Wintag Order Code:	A1-HB	Available Variants	Available Variants	Available Variants	Available Variants	Available Variants	Available Variants	Available Variants
Description	A1-HB HF made in Nylon GF Basic IP65, usable -40°/+120°	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D
Materiale housing:	Nylon GF+PU resin	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D
Wintag Order Code:	A1-H3							
Description	A1-H3 HF made in Nylon GF Resined IP68, usable -40°/+120°	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D
Materiale housing:	Nylon GF+PU resin	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D
Wintag Order Code:								
Description	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D
Materiale housing:	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D
Wintag Order Code:								
Description	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D
Materiale housing:	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D	#N/D